



Curvascape LE Gas Fire Range

CURVASCAPE LOW ENERGY TIMER FIRE



The Curvascape Low Energy Gas fire range includes two variants:

- Low Energy output
- Low Energy output with Timer control

The LE (low energy) range was introduced to offer reduced gas consumption and so be more environmentally friendly.

SPECIFICATION

| | |
|---|---|
| Overall height: | |
| GL | 552mm |
| GPW | 552mm |
| Overall width: | |
| GL | 582mm |
| GPW | 582mm |
| Overall depth: (including spigot length) | |
| GL | 224mm |
| GPW | 224mm |
| Weight: | 11Kg |
| Wall opening: | 535mm High x 512mm Wide |
| Heat input: | Max: 2.8 kW Gross Min: 1.8 kW Gross |
| Appliance efficiency classification: | 2 |
| Gas Connection: | Suitable for connection to 5/16" or 8mm copper pipe with olive and nut. |
| Burner: | Worgas Type POO -2041 W00283 |
| Injector: | Widney W00738 (1.02 / 0.77mm) LPG Widney W00748 (1.48 / 1.23mm) NG |
| Control Valve with Rotary Piezo: | Copreci W00407 LPG Copreci W00166 NG |
| Pilot/Oxygen depletion device: | W00747 LPG W00749 NG |
| Pressure test point: | On Control Valve |

GAS CONSUMPTION

| Gas type | High | Low |
|---------------|--------------------------|--------------------------|
| G20 | 0.267 m ³ /hr | 0.17 m ³ /hr |
| G25 | 0.310 m ³ /hr | 0.201 m ³ /hr |
| G30 | 0.079 m ³ /hr | 0.051 m ³ /hr |
| G31 (37 mbar) | 0.105 m ³ /hr | 0.068 m ³ /hr |
| G31 (30 mbar) | 0.095 m ³ /hr | 0.062 m ³ /hr |